









# Cooper Pegler Reflex Nozzles



55 - 130 Degrees

Wide angled flat flood spray specifically designed for applications through hand-held sprayers over 1-3 bar. Available in different spray angles that give ground coverage of between 50 cm and 2 m with a 50 cm boom height,. Flow rates from 0.6 to 3.79 l/min. Can be used with spray shield to reduce spray drift

Colour	Part No.	BCPC Code	BCPC Spray	Pressure (bar)	Flow (L/min)	Coverage @ 0.5m	Application Rates (L/ha) at			
							2 Km/h	3 Km/h	4 Km/h	6 Km/h
	AN0.6 (100#) 371853 372020	D/0.60/1	Coarse	1.00	0.600		360	240	180	144
			Coarse	1.50	0.730		438	292	219	175
			Medium	2.00	0.850		510	340	255	204
			Medium	2.50	0.950		570	380	285	228
	AN1.2 (50#) 371854 372021	D/1.20/1	Coarse	1.00	1.200		360	240	180	144
			Coarse	1.50	1.470		441	294	221	176
			Medium	2.00	1.700		510	340	255	204
			Medium	2.50	1.900		570	380	285	228
	AN1.8 (50#) 371855 372022	D/1.80/1	Coarse	1.00	1.800		360	240	180	144
			Coarse	1.50	2.199		440	293	220	176
			Coarse	2.00	2.550		510	340	255	204
			Coarse	2.50	2.850		570	380	285	228
	AN2.4 (50#) 371856 372023	D/2.40/1	Coarse	1.00	2.400		360	240	180	144
			Coarse	1.50	2.940		510	294	221	204
			Coarse	2.00	3.390		509	339	254	203
			Coarse	2.50	3.790		570	380	285	228